SPECIFICATIONS

Model #	DCS400	DCS400-09	DCS400-05	DCS355	DCS300	DCS200	DCS200-05	DCS200-09	DCS100	DCS050	Model #
Name	The Seeker 400 Wireless, Recording, Video Inspection System	The Seeker 400-09 Wireless, Recording, Video Inspection System	The Seeker 400-05 Wireless, Recording, Video Inspection System	The Seeker 355 Video Inspection System	The Seeker 300 Video Inspection System	The Seeker 200 Video Inspection System	The Seeker 200-05 Video Inspection System	The Seeker 200-09 Video Inspection System	The Seeker 100 Wireless USB Video Inspection System	The Seeker 050 USB Video Inspection System	Name
Standard Probe Diameter	12mm	9mm	5.5mm	5.5mm	12mm	12mm	5.5mm	9mm	12mm	12mm	Standard Probe Diameter
Standard Probe Type	Flexible-Obedient	Flexible-Obedient	Flexible-Obedient	Flexible-Obedient	Flexible-Obedient	Flexible-Obedient	Flexible-Obedient	Flexible-Obedient	Flexible-Obedient	Flexible-Obedient	Standard Probe Style
Standard Probe Length	3.28 ft. (1m)	3.28 ft. (1m)	3.28 ft. (1m)	3.28 ft. (1m)	3.28 ft. (1m)	3.28 ft. (1m)	3.28 ft. (1m)	3.28 ft. (1m)	3.28 ft. (1m)	3.28 ft. (1m)	Standard Probe Length
Display	3.5 in. color LCD	3.5 in. color LCD	3.5 in. color LCD	3.5 in. color LCD	3.5 in. color LCD	2.4 in. color LCD	2.4 in. color LCD	2.4 in. color LCD	User's computer	User's computer	Display
Wireless Range	Up to 33 ft. (10m)	Up to 33 ft. (10m)	Up to 33 ft. (10m)	–	–	–	–	–	Up to 33 ft. (10m)	–	Wireless Range
VOIP Capability	Yes	Yes	Yes	–	–	–	–	–	Yes	–	VOIP Capability
Recording	Video and still images	Video and still images	Video and still images	–	–	–	–	–	Video and still images	–	Recording
Resolution (pixels)	Video: 320 x 240 Still images: 704 x 576	Video: 320 x 240 Still images: 704 x 576	Video: 320 x 240 Still images: 704 x 576	Video: 320 x 240 Still images: 704 x 576	Video: 320 x 240 Still images: 704 x 576	Video: 320 x 240 Still images: 704 x 576	Video: 320 x 240 Still images: 704 x 576	Video: 320 x 240 Still images: 704 x 576	Video: 320 x 240 Still images: 704 x 576	Video: 320 x 240 Still images: 704 x 576	Resolution (pixels)
Magnets and Stand for Added Convenience	Yes	Yes	Yes	–	–	–	–	–	–	–	Magnets and Stand for Added Convenience
Battery	Rechargeable	Rechargeable	Rechargeable	Alkaline battery	Alkaline battery	Alkaline battery	Alkaline battery	Alkaline battery	Rechargeable	No battery needed	Battery
Date/Time Stamp	Yes	Yes	Yes	N/A	N/A	N/A	N/A	N/A	Yes	Yes	Date/Time Stamp
Field of View	60°	60°	60°	60°	60°	60°	60°	60°	60°	60°	Field of View
Depth of Field	0.5 to 5 in. (1/8 in. to 1.25 in. w/4X zoom)	4 in. to infinity (1 in. to infinity w/4X zoom)	0.5 to 5 in. (1/8 in. to 1.25 in. w/4X zoom)	0.5 to 5 in. (1/4 in. to 2.5 in. w/2X zoom)	4 in. to infinity (2 in. to infinity w/2X zoom)	4 in. to infinity (2 in. to infinity w/2X zoom)	0.5 to 5 in. (1/4 in. to 2.5 in. w/2X zoom)	4 in. to infinity (2 in. to infinity w/2X zoom)	4 in. to infinity	4 in. to infinity	Depth of Field
Zoom and Rotation	4X Zoom, 180° rotation	4X Zoom, 180° rotation	4X Zoom, 180° rotation	2X Zoom, 180° rotation	2X Zoom, 180° rotation	2X Zoom, 180° rotation	2X Zoom, 180° rotation	2X Zoom, 180° rotation	Via user's computer	Via user's computer	Zoom and Rotation
Water and Dust Proof	as per IP67	as per IP67	as per IP67	as per IP67	as per IP67	as per IP67	as per IP67	as per IP67	as per IP67	as per IP67	Water and Dust Proof
Light Source	Two adjustable LEDs	Two adjustable LEDs	Two adjustable LEDs	Two adjustable LEDs	Two adjustable LEDs	Two adjustable LEDs	Two adjustable LEDs	Two adjustable LEDs	Two adjustable LEDs	Two adjustable LEDs	Light Source
Operating Temperature	32° to 113°F (0° to 45°C)	32° to 113°F (0° to 45°C)	32° to 113°F (0° to 45°C)	32° to 113°F (0° to 45°C)	32° to 113°F (0° to 45°C)	32° to 113° F (0° to 45°C)	32° to 113° F (0° to 45°C)	32° to 113° F (0° to 45°C)	32° to 113°F (0° to 45°C)	32° to 113°F (0° to 45°C)	Operating Temperature
Memory (capacity of included SD card)	2 GB	2 GB	2 GB	–	–	–	–	–	–	–	Memory (capacity of included SD card)
Certifications	CE, FCC	CE, FCC	CE, FCC	CE	CE	CE	CE	CE	CE, FCC	CE	Certifications
Warranty	3 year limited	3 year limited	3 year limited	3 year limited	3 year limited	3 year limited	3 year limited	3 year limited	3 year limited	3 year limited	Warranty

SPECIFICATIONS