

Coal Mine Dust Sampling System

Escort® ELF Pump

The Escort ELF pump is designed for use in coal mine dust sampling as specified in 30 CFR Part 74. The state of the art electronic laminar flow sensor provides a constant flow control with $\pm 2.5\%$ regulation of flow rate (from 1-3 lpm) with automatic compensation for changes in battery voltage, temperature, altitude, and sample load. An internal secondary standard calibrates the pump continuously and needs to be checked against a primary standard only once per month (or every 200 hours for coal mine dust sampling).

Escort Elf Sampling Pumps are NIOSH certified for coal mine dust sampling (TC-74-030) and MSHA certified as intrinsically safe for underground use (Approval # 2G-3924-1). UL approved as intrinsically safe for use in hazardous locations, Class I, Groups A, B, C, D; Class II, Groups E, F and G; Class III, Division I locations.

- Patented Electronic laminar flow control.
- Internal secondary standard calibrates the pump continuously.
- Inlet filter traps moisture and particulate matter
- Stainless steel filled plastic case provides EMI/RFI protection
- Rated IP66 for resistance to water and dust ingress.
- Flow fault indicator shows any sample inlet blockage
- Check against primary standard once per month or every 200 hours for coal mine dust sampling.



10mm Nylon Cyclone

Zefon's 10mm Nylon Cyclone (model 456243) is designed specifically for use with preweighed filter cassette assemblies when sampling for coal mine dust. The cyclone is used to separate respirable dust particles from non-respirable particles and is specified for use in coal mine dust sampling per 30 CFR, part 74.



Filter Cassette Assembly

Zefon's Preweighed Coal Dust Sampling Cassettes consist of a sealed outer plastic capsule and an inner pre-weighed filter capsule. The inner capsule contains a 5 micron PVC filter, and stainless steel supports. Each filter cassette is supplied with a mine data card, which has the weight of the filter capsule recorded to the nearest 0.1mg, and a mailing carton addressed to MSHA (Mine Safety and Health Administration). Specified for use in coal mine dust sampling per 30 CFR part 74.



Zefon
INTERNATIONAL

The Professionals Choice for Air Sampling Equipment

5350 SW 1st Lane, Ocala, FL 34474 USA | Tel: 352.854.8080 | Fax: 352.854.7480 | www.zefon.com

Escort® Pump Accessories



Calibration Devices

The calibration of a sampling pump is critical to the quality of samples taken. Calibration determines that the flow rate of air through the pump is accurate, within specified limits, usually $\pm 5\%$. A primary calibration device, the DigiCal™ Calibrator provides instantaneous calibration for instruments like the Zefon Escort LC Pump or the secondary flow standard inside the Escort ELF Sampling Pumps.

Just press the plunger and the DigiCal Calibrator does the work. Its unique flow cell replaces conventional bubble tubes and makes calibration easier. The DigiCal Calibrator achieves extreme accuracy by utilizing a computerized flow meter that provides instantaneous flow readouts on a digital display. Accurate measurements are possible within $\pm 0.5\%$ at any altitude.

Escort ELF Specifications

- Operating Flow Control**
 Volumetric flow rate held within $\pm 2.5\%$ of set-point over the 1-to-3 LPM operating range ($\pm 5\%$ to 0.5 LPM), with automatic compensation for battery voltage, altitude, temperature and sample load changes.
- Flow Rate**
 Flow rate adjustable between 0.5 and 3 LPM; lower flow rates attainable (to 1 MLPM) with optional Gemini Twin-Port Sampling accessory.
- Flow Indication**
 Liquid Crystal Display provides 0.01 LPM resolution.
- Operating Range**
 30 inches of water load up to 2 LPM and 10 inches up to 3 LPM.
- Flow Blockage Detection**
 Flow-Fault LED comes on immediately when block is detected. Pump shuts down within 90 seconds if block is not cleared.
- Elapsed Time Readout**
 To 999 minutes in increments of 1 minute. Holds the last reading after either flow blockage or low battery shutdown and when pump is off or in hold mode.
- Operating Time**
 Varies with flow rate and sampling device loading.
- Physical Weight**
 23 oz. (652 gm), with battery pack.
- Dimensions**
 2.25" D x 4.25" H x 4" W (5.7 cm x 10.8 cm x 10.2 cm), with battery pack.
- Power Supply**
 4.8-volt battery pack of four nickel metal hydride cells.
- Battery Pack Capacity**
 2.8 amp hours
- Battery Pack Recharge Time**
 14-16 hours (overnight) with Omega™ Charger.
- Typical Battery Pack Life**
 300 or more charging cycles

Pumps

PRODUCT	DESCRIPTION	PRICE
805560	Escort ELF Pump with 120v charger and sampling line	\$976.00
805563	Escort ELF 5 Pack Pump Kit with 5 station 120/240v charger and sampling lines	\$4,960.00

Pump Calibrators

PRODUCT	DESCRIPTION	PRICE
655101	DigiCal Calibrator	\$1,100.00

Cyclone

PRODUCT	DESCRIPTION	PRICE
456243	Respirable Dust Sampling Cyclone Assembly for Coal Dust Cassettes	\$270.00

Filter Cassette Assembly

PRODUCT	DESCRIPTION	PRICE
803462-2PK	Coal Dust Sampling Cassette for Mine Operators, pre-weighed with 5.0 um PVC filter and Mine Data Card, 2/pk	\$55.00

Escort and DigiCal are trademarks of Zefon International.



5350 SW 1st Lane, Ocala, FL 34474 USA
 Tel: 352.854.8080 | Fax: 352.854.7480 | www.zefon.com

*The Professionals Choice
 for Air Sampling Equipment*