



TRIDENT® HAZ-LO® HEADLAMP
AAA BATTERY-POWERED C1D1 HEADLAMP

MARKET

APPLICATIONS: Professional Light - Industrial, Hardware/Tool, Automotive, Sporting Goods, Consumer, Emergency Medical Services, Safety, Pest Control, Boating, Aviation.

DESCRIPTION: The Trident® Haz-Lo® headlamp with adjustable head straps features two lighting levels. Use the (3) three Ultra Bright 5mm LEDs for “up close task lighting” and the single C4® power LED for long distance lighting needs. You get this all this in one convenient package.

CASE MATERIAL: Tough thermoplastic construction with elastomer over mold. Available in Yellow.

DIMENSIONS: Face Cap Diameter: 1.75 in. (4.45cm) Maximum Width: 2.70 in (6.85 cm)
 Maximum Depth (including head strap mounting plate): 2.40 in. (6.09 cm)

WEIGHT: 5.50 oz (156 grams) with batteries (included with purchase).

LENS: Unbreakable polycarbonate lens.

LIGHT SOURCE: One (1) White C4® LED technology, impervious to shock with a 50,000 hour lifetime.
 Three (3) 5mm Ultra Bright White LEDs, impervious to shock with 100,000 hour lifetime.

LIGHT OUTPUT: Low: (3) 5 mm LEDs - 30 lumens, 300 candela peak beam intensity, and 35 meter beam distance.
 High: (1) C4® LED - 85 lumens, 2600 candela peak beam intensity, and 102 meter beam distance.



ON/OFF: Push-button switch - Sequences through Low, High and Off.


RUN TIME: See chart for run time data. All runtime claims are to 10% of initial lumen output.

BATTERY: Three (3) “AAA” size, Alkaline batteries.

FEATURES: C4® LED technology for extreme brightness.
 IPX4 rated for water resistant operation.
 2 meter impact resistance tested.
 90° tilting head.
 Rubber Hard Hat Strap (included in purchase).







WARRANTY: Streamlight's Limited Lifetime Warranty

APPROVALS:  Class 1, Division 1, Groups A,B,C,D; Class II, Division 1, Groups E,F,G; Class III, T-Class: T4 Exia. (Using: Rayovac No. 824, Panasonic AM-4PA, Energizer EA92, or Energizer Lithium L92 batteries.)

 Meets applicable European Community directives.

OPTIONAL ACCESSORIES: N/A

OUTPUT
 RUNTIME
 DISTANCE
 INTENSITY

FL1 STANDARD	LOW	HIGH
	30 LUMENS	85 LUMENS
	24h	8h
	35m	102m
	300cd	2,600cd

